



iCOOL

HORIZONTAL DIRECT EXPANSION BULK MILK TANKS

The Milfos DX-FF, manufactured by Fabdec, offers the dairy farmer the ultimate in milk cooling technology.

High quality stainless steel, extreme efficiency and outstanding reliability ensure that the range of DX-FF tanks give top cooling and washing performance.

With a range of sizes from 1,200 to 30,000 litres, a range of profiles, bulk-head access styles and well thought out design, DARI-KOOL DX-FF tanks offer the flexibility to fit any location. With a vast array of options; compromise is not one of them!

With over forty years in stainless steel fabrication and heat transfer technology, you can be sure that we have the experience to create the bulk milk tank you can rely on.



KEY FEATURES

- Complete range from 1,200 to 30,000 litres
- Highest quality and performance
- Built to fit
- Designed with technology

TECHNICAL INFORMATION

CAPACITY (LITRES)	DESCRIPTION	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	CAPACITY (LITRES)	DESCRIPTION	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)
1,200	DX-FF 1200 Standard Profile	1155	2393	1670	8,000	DX-FF 8000 Low Profile	1840	4480	2260
1,600	DX-FF 1600 Standard Profile	1305	2493	1770	10,000	DX-FF 10000 Standard Profile	2435	3418	2838
2,000	DX-FF 2000 Standard Profile	1420	2550	1800	10,000	DX-FF 10000 Low Profile	2035	5307	2210
2,500	DX-FF 2500 Standard Profile	1575	2543	1945	12,000	DX-FF 12000 Low Profile	2838	4048	2450
3,000	DX-FF 3000 Standard Profile	1575	2953	1945	12,000	DX-FF 12000 Low Profile	2435	4871	2000
3,500	DX-FF 3500 Standard Profile	1575	3358	1945	13,000	DX-FF 13000 Standard Profile	2435	4347	2705
4,000	DX-FF 4000 Standard Profile	1840	2693	2250	14,000	DX-FF 14000 Standard Profile	2435	4657	2790
4,500	DX-FF 4500 Low Profile	1840	3617	1895	16,000	DX-FF 16000 Standard Profile	2435	5227	2775
5,000	DX-FF 5000 Standard Profile	1840	3233	2250	18,000	DX-FF 18000 Standard Profile	2565	5399	2930
6,000	DX-FF 6000 Standard Profile	2035	3418	2260	20,000	DX-FF 20000 Standard Profile	2435	6397	2810
7,000	DX-FF 7000 Standard Profile	2435	3044	2415	22,000	DX-FF 22000 Standard Profile	2565	6368	2990
8,000	DX-FF 8000 Standard Profile	2435	3419	2415	28,000	DX-FF 28000 Standard Profile	2840	6327	3265

